MOTOR DATA @ 230 VAC (TRAP)

MOTOR PARAMETERS		UNITS	VALUE
HORSEPOWER	HP RATED	Hp	1.2
KILOWATTS	KW RATED	KW	.88
MAX. OPERATING SPEED	N MAX	RPM	2100
SPEED @ RATED TORQUE	N RATED	RPM	1500
* CONTINUOUS RATED TORQUE @ 1500 RPM		IN-LBS[Nm]	50.0[5.6]
* CONTINUOUS STALL TORQUE		IN-LBS[Nm]	54.0[6.1]
CONTINUOUS LINE CURRENT		AMPS	4.4
PEAK TORQUE	Tpk	IN-LBS[Nm]	189.1[21.3]
PEAK CURRENT		AMPS	15.3
MAX. THEORETICAL ACCEL.		RAD/SEC²	48,487
TORQUE SENSITIVITY	Kt	IN-LBS/AMP[Nm/AMP]	12.4[1.42]
BACK EMF (LINE TO LINE)	±10%	Vrms/Krpm	110.0
D.C. RESISTANCE (P-P)	±10%	OHMS	3.3
INDUCTANCE (P-P)	±10%	MILLIHENRIES	24.4
ROTOR INERTIA W/BRAKE	Jm	IN-LBS-SEC²[Kg-M²]	.0039[.00044]
STATIC FRICTION	Tf	IN-LBS[Nm]	1.0[.11]

*25°C AMBIENT WITH A MAXIMUM CASE TEMPERATURE OF 100°C ON MOTOR. MOTOR MOUNTED ON A 12" X 12" X 1/2" ALUMINUM HEATSINK. THERMOSTAT IN STATOR WINDINGS WILL OPEN IF WINDING TEMPERATURE EXCEEDS 155°C. THIS ALLOWS FOR AN APPROXIMATE +10% HEADROOM IN THE CONTINUOUS TORQUE RATING BEFORE THERMOSTAT OPENS.

MECHANICAL NOTES:
1. AXIAL LOAD: 50 LBS MAX
2. RADIAL LOAD: 100 LBS MAX @ 1" FROM FACE
3. MOTOR SEALED TO IP65.
4. MOTOR WEIGHT: 23.3 LBS. [10.6 Kg]
5. MOTOR FINISH: BLACK EPOXY
6. MOTOR OUTPUT SHAFT: STAINLESS STEEL
7. INCHES (MILLIMETERS)

ENCODER: (290-00052)
OIH48-2000P6-L6-5V

FAILSAFE BRAKE:
MIN HOLDING TORQUE: 240 IN-LBS
INPUT VOLTAGE: 24 VOLTS

CONNECTION CHART

MOTOR/BRAKE CONNECTOR:
PT02E-16-8P(027)
(270-00032)

MOTOR/BRAKE WIRE LEADS		
PIN	WIRE FUNCTION	WIRE COLOR
A	ΦR	RED
B	ΦS	BLACK
C	ΦT	BLUE
D	PE GND	GRN/YEL
E	BRK SHLD	–
F	BRK (+)	DIODE
G	BRK (–)	1N4007
H	–	–

ENCODER/THERM CONNECTOR:
PT02E-14-18P(027)
(270-00024)

ENC/THERM WIRE LEADS		
PIN	WIRE FUNCTION	WIRE COLOR
T	GROUND	BLACK
K	+5VDC	RED
B	CH A	BLUE
C	CH A\	BLUE/BLK
N	CH B	GREEN
P	CH B\	GRN/BLK
M	CH Z	YELLOW
U	CH Z\	YEL/BLK
E	CH U	BROWN
R	CH U\	BRN/BLK
F	CH V	GRAY
S	CH V\	GRAY/BLK
G	CH W	WHITE
H	CH W\	WHT/BLK
D	GND/CABLE	SHLD
A	THERM	BLACK
L	THERM	BLACK
J	GND	GRN/YEL



MOTOR & HALL POSITION CHART

HALL LEADS	BROWN	GRAY	WHITE
MOTOR LEADS	BLACK respect to RED	RED respect to BLUE	BLUE respect to BLACK
VIEW ON THE OSCILLOSCOPE			

*MOTOR ROTATION CCW (COUNTER CLOCKWISE)
(LOOKING AT THE FACE OF THE MOTOR)

WAVE REPRESENTING STATOR OUTPUT
WAVE REPRESENTING HALL SENSOR



TITLE: "B"/TRAP/230/ENG/T2/CONN/BRK	DRAWING NUMBER: MPM1141BTG6JN1R

REVISIONS

REV.	DESCRIPTION	DATE	APPD.
	PRELIMINARY	7/13/99	MVS

NO.	PART NUMBER	DESCRIPTION	QTY.

TOLERANCES UNLESS SPECIFIED
DECIMAL .XXX ± .005
DECIMAL .XX ± .010
DECIMAL .X ± .020
FRACTION ± 1/64
ANGLE ± 1/2

MTS Systems Corporation
Automation Division

PROPRIETARY RIGHTS OF MTS AUTOMATION ARE INCLUDED IN THE INFORMATION DISCLOSED HEREIN. THIS DRAWING AND/OR DOCUMENT SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR USED OR DISCLOSED TO OTHERS FOR ANY PURPOSE EXCEPT FOR WHICH WAS SPECIFICALLY FURNISHED.

DRAWN: MVS	TITLE: "B"/TRAP/230/ENG/T2/CONN/BRK	REV.
DATE: 7/13/99		
CHECKED:	MATERIAL:	
APPROVED:	DRAWING NUMBER: MPM1141BTG6JN1R	SCALE: 1/2:1